

ANTIFREEZE



PENTOFROST A1

Antifreeze Specially Formulated For Asian Vehicles
– 50/50 Prediluted

DESCRIPTION

Pentofrost A1 is a phosphated organic acid technology (phosphated OAT); which is categorized as HOAT (hybrid organic acid technology) in the US market. Pentofrost A1 is suitable for all Asian vehicles using “red” Antifreeze/Coolant. Pentofrost A1 does not contain any silicate, borate, nitrite, or amine additives since these may harm your Asian vehicle. Do not mix with other coolants (especially silicated coolants), as this may cause gel formation and clog your radiator. Pentofrost A1 is a **PREDILUTED** antifreeze for Asian vehicle applications in water-cooled engines. It contains phosphates and organic salts to protect all materials used in cooling systems for Asian vehicles. Pentofrost A1 is mixable with all phosphate OATs. Meets ASTM D-3306.

PRODUCT ATTRIBUTES

Appearance	Red
Density at 20°C	1127 kg/m ³
Freezing Point	<-15°C/<5°F
Flash Point	128°C/262°F
Boiling Point	173.5°C/344.3°F
Water Content	Max 52%
pH Value	7.9
Mixing Ratio With Water	50/50
Boiling Point With Water	109°C/228°F
Freezing Point With Water	-37.6°C/-35.7°F

SIZE

PART NUMBER

GTIN-12

1 Gallon	8115213	888544065927
1 Gallon (Canada)	8115214	88544065941

OE REFERENCE NUMBERS/RECOMMENDATIONS

Make	Reference Number
------	------------------

Toyota/Lexus/Scion	00272-1LLAC
Toyota/Lexus/Scion	00272-1LLAC-01

Always consult the vehicle owner’s manual to identify fluid specification requirements. MSDS available to professional repair technician upon request.

© CRP Industries Inc. Pentosin is a trade name of FUCHS Schmierstoffe GmbH. All rights reserved.

DISCLAIMER: CRP Industries Inc. has made every effort to assure the accuracy of the information on this product data sheet. Neither CRP Industries Inc., nor its affiliates assume responsibility for any loss or damage due to any errors, omissions, or manufacturing changes.

PENTOFROST1PD-102517



OE-quality brands for import applications.