

ANTIFREEZE



PENTOFROST A4

Antifreeze Specially Formulated For Asian Vehicles
– 50/50 Prediluted

DESCRIPTION

Pentofrost A4 is a phosphated organic acid technology (phosphated OAT); which is categorized as HOAT (hybrid organic acid technology) in the US market. Pentofrost A4 is suitable for all Asian vehicles using “pink” Antifreeze/Coolant. Pentofrost A4 does not contain any silicate, borate, nitrite, or amine additives since these may harm your Asian vehicle. Do not mix with other coolants (especially silicated coolants), as this may cause gel formation and clog your radiator. Pentofrost A4 is a **PREDILUTED** antifreeze for Asian vehicle applications in water-cooled engines. It contains phosphates and organic salts to protect all materials used in cooling systems for Asian vehicles. Pentofrost A4 is mixable with all phosphated OAT’s. Meets ASTM D-3306.

PRODUCT ATTRIBUTES

Appearance	Pink
Density at 20°C	1140 kg/m ³
Flash Point	129°C/264°F
Water Content	Max 52%
pH Value	7.9
Mixing Ratio With Water	50/50
Boiling Point With Water	109°C/228°F
Freezing Point With Water	-37.4°C/-35.3°F

SIZE	PART NUMBER	GTIN-12
1 Gallon	8115209	843266042731
1 Gallon (Canada)	8115210	843266042748

OE REFERENCE NUMBERS/RECOMMENDATIONS

Make	Reference Number
Toyota/Lexus/Scion	00272-SLLC2

Always consult the vehicle owner’s manual to identify fluid specification requirements. MSDS available to professional repair technician upon request.

© CRP Industries Inc. Pentosin is a trade name of FUCHS Schmierstoffe GmbH. All rights reserved.

DISCLAIMER: CRP Industries Inc. has made every effort to assure the accuracy of the information on this product data sheet. Neither CRP Industries Inc., nor its affiliates assume responsibility for any loss or damage due to any errors, omissions, or manufacturing changes.

PENTOFROSTA4-121217



OE-quality brands for import applications.