

MOTOR OIL



# PENTO HIGH PERFORMANCE 5W-30

## Fully Synthetic Fuel Economy Engine Oil

### DESCRIPTION

**Pento High Performance 5W-30** is a fully synthetic high performance engine oil, developed for the most recent vehicles with extended oil service intervals. Pento HP can be used in all gasoline and diesel engines containing turbochargers as well as non-turbocharged vehicles requiring 5W-30.

SIZE	PART NUMBER	GTIN-13
1 Liter	8043107	4008849115233
5 Liter	8043206	4008849155239
20 Liter	8043208	4008849165221

### PRODUCT ATTRIBUTES

Appearance	Amber & Clear
Density at 15°C	852 kg/m <sup>3</sup>
Density at 20°C	849 kg/m <sup>3</sup>
Kinematic Viscosity at 100°C	12.3 mm <sup>2</sup> /s
Kinematic Viscosity at 40°C	73 mm <sup>2</sup> /s
Viscosity Index	171
Dynamic Viscosity at -30°C	5700 mPa*s
Pour Point	-42°C/-43.6°F
Flash Point	240°C/464°F

### OE REFERENCE NUMBERS/RECOMMENDATIONS

Make	Reference Number
Audi/Volkswagen	ZVW 352 167
BMW	07 51 0 017 866
BMW	83 21 0 144 450
BMW	83 21 0 144 452
Mercedes-Benz	000 989 78 01
Mercedes-Benz	000 989 83 01
MINI	83 21 0 144 468

### APPROVALS/SPECIFICATIONS

Organization Name	Specification Met
Audi/Volkswagen	502.00, 505.00
BMW	Longlife-01
Mercedes-Benz	229.5
Opel/GM	GM-LL-B-025
ACEA	A3/B3, A3/B4
API	SL/CF

Always consult the vehicle owner's manual to identify fluid specification requirements. MSDS available to professional repair technician upon request.

© CRP Industries Inc. Pentosin is a trade name of FUCHS Schmierstoffe GmbH. All rights reserved.

**DISCLAIMER:** CRP Industries Inc. has made every effort to assure the accuracy of the information on this product data sheet. Neither CRP Industries Inc., nor its affiliates assume responsibility for any loss or damage due to any errors, omissions, or manufacturing changes.

PENTOHP5W30-0526



AAE | REIN | PENTOSIN

OE-quality brands for import applications.