

MOTOR OIL



PENTO SUPER PERFORMANCE 5W-40

Fully Synthetic Extended Life Engine Oil

DESCRIPTION

Pentospeed Super Performance 5W-40 is an Super Performance engine oil that provides outstanding fuel economy and reduced emissions. It provides excellent cold starting behavior, extremely fast oil circulation and high thermal stability. Pentospeed SP 5W-40 is thermal stable, reduces wear and can be used for extended drain intervals.

PRODUCT ATTRIBUTES

Appearance	Brown
Density at 15°C	0.852 g/ml
Kinematic Viscosity at 40°C	82.8 mm ² /s
Kinematic Viscosity at 100°C	13.8 mm ² /s
Dynamic Viscosity at -30°C	6000 mPa*s
Flash Point	200°C
Viscosity Index	171

SIZE	PART NUMBER	GTIN-13
1 Liter	8044107	4001541459971
5 Liter	8044206	4001541459988

OE REFERENCE NUMBERS/RECOMMENDATIONS

Make	Reference Number
Audi/Volkswagen	G052 167 M2
BMW	07 51 0 017 866
Mercedes-Benz	000 989 83 01

APPROVALS/SPECIFICATIONS

Organization Name	Specification Met
Audi/Volkswagen	502.00, 505.00
BMW	LL-01
Mercedes-Benz	229.5
Porsche	A40
ACEA	A3/B4
API	CF
GM	GM-LL-B-025

Always consult the vehicle owner's manual to identify fluid specification requirements. MSDS available to professional repair technician upon request.

© CRP Industries Inc. Pentosin is a trade name of FUCHS Schmierstoffe GmbH. All rights reserved.

DISCLAIMER: CRP Industries Inc. has made every effort to assure the accuracy of the information on this product data sheet. Neither CRP Industries Inc., nor its affiliates assume responsibility for any loss or damage due to any errors, omissions, or manufacturing changes.

PENTOSP5W40-0118



OE-quality brands for import applications.