

MOTOR OIL



PENTOSPEED VCC 0W-20

Fully Synthetic Fuel Economy Engine Oil

DESCRIPTION

Pentospeed VCC 0W-20 is innovatively formulated low viscosity motor oil designed specifically for use with the new Volvo VEA engine generation of gasoline and diesel engines. Pentospeed VCC 0W-20's unique formulation offers superior wear protection and performance reserves. This top of the line motor oil is excellent in cold start conditions and boasts reduced CO2 emissions and lower fuel consumption. The significant improvements in fuel economy and CO2 emissions were achieved by lowered the dynamic viscosit and utilizing new additive technology. The viscosity class has been specially adjusted to fulfill the requirements of Volvo.

PRODUCT ATTRIBUTES

| | |
|------------------------------|-------------------------|
| Appearance | Brown |
| Density at 15°C | 0.85 g/ml |
| Kinematic Viscosity at 40°C | 38.7 mm ² /s |
| Kinematic Viscosity at 100°C | 8.5 mm ² /s |
| Dynamic Viscosity at -35°C | 5060 mPas |
| Dynamic Viscosity at 150°C | 2.75 mPas |
| Flash Point | 232°C/449°F |
| Viscosity Index | 208 |

| SIZE | PART NUMBER | GTIN-13 |
|---------|-------------|---------------|
| 1 Liter | 8044313 | 4001541458691 |
| 5 Liter | 8044315 | 4001541458752 |

APPROVALS/SPECIFICATIONS

| Organization Name | Specification Met |
|-------------------|-------------------|
| ACEA | A1/B1 |
| Volvo | VCC RBS0-2AE |

Always consult the vehicle owner's manual to identify fluid specification requirements. MSDS available to professional repair technician upon request.

© CRP Industries Inc. Pentosin is a trade name of FUCHS Schmierstoffe GmbH. All rights reserved.

DISCLAIMER: CRP Industries Inc. has made every effort to assure the accuracy of the information on this product data sheet. Neither CRP Industries Inc., nor its affiliates assume responsibility for any loss or damage due to any errors, omissions, or manufacturing changes.

PENTOVCCOW20-1018



OE-quality brands for import applications.