TRANSMISSION FLUID





PENTOSIN ATF 44

Long-Life Fully Synthetic Automatic Transmission Fluid

DESCRIPTION

Pentosin ATF 44 is mainly designated for use in Aisin AW automatic transmissions being used in a large number of Japanese passenger cars and light duty vehicles. It can also be used in select American and European models. Due to its outstanding properties, Pentosin ATF 44 can be used in many aggregates of Asian origin or where DEXRON III-type fluids are demanded. Pentosin ATF 44 is miscible and compatible with conventional branded gear oils. Mixing with other gear oils should be avoided in order to fully utilize the product's benefits. A complete fluid change is recommended when converting to Pentosin ATF 44.

SIZE	PART NUMBER	GTIN-13
1 Liter	1058112	4001541459308
5 Liter	1058212	4001541459315

PRODUCT ATTRIBUTES			
Appearance	Red		
Density at 15°C	0.852 g/ml		
Kinematic Viscosity at 100°C	7.3 mm ² /s		
Kinematic Viscosity at 40°C	37.3 mm ² /s		
Viscosity Index	165		
Pour Point	-43°C/-45.4°F		

OE REFERENCE NUMBERS/RECOMMENDATIONS		
Make	Reference Number	
Audi/Volkswagen	G 055 025 A2	
Audi/Volkswagen	G 052 990 A2	
BMW/MINI	83220402413	
BMW/MINI	83227542290	
Chrysler	MS7176E/9602 (ATF+3/+4)	
Daihatsu	Alumix ATF Multi	
Ford	Mercon	
Ford	M2C924-A/M2C922-A1	
GM	Dexron III	
GM	9986195	
Honda	ATF Z1	
Hyundai	SP III	
Isuzu	ATF II	
Isuzu	ATF III	
Mazda	ATF D-III	
Mazda	ATF M-3	

OE REFERENCE NUMBERS/RECOMMENDATIONS		
Reference Number		
ATF M-V		
SP-II		
SP-III		
Matic C/D/J		
ATF-HP		
ATF 3317		
Type D-2		
Type T-II		
Type T-III		
Type T-VI		

APPROVALS/SPECIFICATIONS		
Organization Name	Specification Met	
Asian Vehicles	JASO M315 TYPE 1A-LV	

