



PENTOSIN ATF 5

Long-Life Fully Synthetic Automatic Transmission Fluid

DESCRIPTION

Pentosin ATF 5 is a fully synthetic high performance Automatic Transmission Fluid (ATF) for life-time application in automatic gear boxes. Pentosin ATF 5 is formulated by means of the best commercially available synthetic base oils and additive components. A high performance shear stable VI-Improver plus modern antiwear chemistry and friction modifiers guarantee a sound stable friction performance in modern automatic transmissions equipped with an electronically controlled converter clutch.

PRODUCT ATTRIBUTES

Appearance	Amber & Clear
Density at 20°C	850 kg/m ³
Kinematic Viscosity at 100°C	7.6 mm ² /s
Kinematic Viscosity at 40°C	38.0 mm ² /s
Viscosity Index	171
Dynamic Viscosity at -40°C	14000 mPa*s
Pour Point	-51°C/-59.8°F
Flash Point	>220°C/>428°F
Wet Boiling Point	≥170°C/≥338°F
pH Value	Slightly Alkaline

SIZE	PART NUMBER	GTIN-13
1 Liter	1058108	4001541229567
5 Liter	1058208	4001541229574
20 Liter	1058308	4001541459353

OE REFERENCE NUMBERS/RECOMMENDATIONS

Make	Reference Number
Audi/Volkswagen	G 052 162 A1/A2/A6
Audi/Volkswagen	VW TL 521 62
BMW	83229407765
BMW	83229407807
BMW	81229407858
BMW	81229407859
GM	Dexron III
Jaguar	JLM20238
Mercedes-Benz	0019892203
Porsche	99991754700
Rolls-Royce	PL 31493 PA
ZF	S671 090 170

APPROVALS/SPECIFICATIONS

Organization Name	Specification Met
Mercedes-Benz	236.11
ZF	ZF TE-ML09

Always consult the vehicle owner's manual to identify fluid specification requirements. MSDS available to professional repair technician upon request.

© CRP Industries Inc. Pentosin is a trade name of FUCHS Schmierstoffe GmbH. All rights reserved.

DISCLAIMER: CRP Industries Inc. has made every effort to assure the accuracy of the information on this product data sheet. Neither CRP Industries Inc., nor its affiliates assume responsibility for any loss or damage due to any errors, omissions, or manufacturing changes.

PENTOATF5-090519



OE-quality brands for import applications.