

## ANTIFREEZE



# PENTOFROST SF 50/50

## Silicate-Free Antifreeze – 50/50 Prediluted

### DESCRIPTION

**Pentofrost SF 50/50** is a **PREDILUTED** Antifreeze for multipurpose applications in water-cooled engines. It does not contain any nitrites, amines, or phosphorous additives. In addition, it does not contain any silicates. Pentofrost SF protects all material used in cooling systems and is recommended for non-ferrous metals and year-round use. Meets ASTM D-3306.

### PRODUCT ATTRIBUTES

Appearance	Pink & Clear
Density at 20°C	1115 kg/m <sup>3</sup>
Flash Point	>110°C/>230°F
Boiling Point	>175°C/>347°F
Water Content	Max 52%
pH Value	8.0
Boiling Point With Water	109°C/228.2°F
Freezing Point With Water	-37°C/-34°F

SIZE	PART NUMBER	GTIN-13
1 Gallon	8114307	
1 Gallon (Canada)	8114310	

### OE REFERENCE NUMBERS/RECOMMENDATIONS

Make	Reference Number
Audi/Volkswagen	G12
Audi/Volkswagen	G12+
Audi/Volkswagen	TL 774 F
Audi/Volkswagen	G 012 A8F A1
Audi/Volkswagen	G 012 A8F A8
Audi/Volkswagen	G 012 A8F M1
Audi/Volkswagen	G 012 A8F M8
Audi/Volkswagen	G 012 A8F M9
BASF	G40
Ford	WSS M97B44-D
Jaguar	JLM20972/1

### OE REFERENCE NUMBERS/RECOMMENDATIONS

Make	Reference Number
Land Rover	STC 50527
Land Rover	STC 50529
Land Rover	STC 50530
Porsche	000 043 203 78
Porsche	000 043 300 31
Porsche	000 043 300 88
Porsche	A 000 043 203 79
Saab	12799123
Saab	12799124

Always consult the vehicle owner's manual to identify fluid specification requirements. MSDS available to professional repair technician upon request.

© CRP Industries Inc. Pentosin is a trade name of FUCHS Schmierstoffe GmbH. All rights reserved.

**DISCLAIMER:** CRP Industries Inc. has made every effort to assure the accuracy of the information on this product data sheet. Neither CRP Industries Inc., nor its affiliates assume responsibility for any loss or damage due to any errors, omissions, or manufacturing changes.

PENTOFROSTESFPD-0924



AAE | REIN | PENTOSIN

OE-quality brands for import applications.