

MOTOR OIL



PENTO HIGH PERFORMANCE II 5W-40

Fully Synthetic Four-Season Engine Oil

DESCRIPTION

PENTO HP II 5W-40 is a Premium Performance engine oil for passenger vehicles. PENTO HP II 5W-40 offers the highest performance across the full operating temperature range from cold start to high temperature operation. The unique lubrication properties of PENTO HP II 5W-40 offer significant benefits in highly loaded engines, especially in the latest downsized engines with or without stop-start systems. Due to its additive technology with reduced SAPS content, PENTO HP II 5W-40 protects exhaust gas aftertreatment systems and improves their durability.

PRODUCT ATTRIBUTES

Appearance	Amber & Clear
Density at 15°C	850 kg/m ³
Kinematic Viscosity at 100°C	13.1 mm ² /s
Kinematic Viscosity at 40°C	72.5 mm ² /s
Viscosity Index	185
Pour Point	-42°C/-43.6°F
Flash Point	228°C/442°F

SIZE	PART NUMBER	GTIN-13
1 Liter	8042107	4001541462421
5 Liter	8042206	4001541462414
20 Liter	8042208	4001541462704
60 Liter	8042303	4001541463930
210 Liter	8042305	4001541462735

OE REFERENCE NUMBERS/RECOMMENDATIONS

Make	Reference Number
Audi/Volkswagen	VW 505.00 / 505.01
BMW	81 22 9 407 547
Chrysler	MS-10725
Ford	WSS-M2C917-A
Mercedes-Benz	000 989 82 01

APPROVALS/SPECIFICATIONS

Organization Name	Specification Met
Audi/Volkswagen	511.00
BMW	LL-04
Mercedes-Benz	226.5 / 229.31 / 229.51 / 229.52
Porsche	C40
ACEA	C3
API	SN

Always consult the vehicle owner's manual to identify fluid specification requirements. MSDS available to professional repair technician upon request.

© CRP Industries Inc. Pentosin is a trade name of FUCHS Schmierstoffe GmbH. All rights reserved.

DISCLAIMER: CRP Industries Inc. has made every effort to assure the accuracy of the information on this product data sheet. Neither CRP Industries Inc., nor its affiliates assume responsibility for any loss or damage due to any errors, omissions, or manufacturing changes.

PENTOHPII5W40-040924



AAE | REIN | PENTOSIN

OE-quality brands for import applications.