

TRANSMISSION
FLUID



PENTOSIN ATF 84

Long-Life Fully Synthetic Automatic Transmission Fluid

DESCRIPTION

Pentosin ATF 84 has been specially designed to deliver performance and increased fuel efficiency for modern automatic transmissions of Japanese and American manufacturers where reduced viscosity is required and meets the stringent DEXRON-ULV and MERCON-ULV specifications. Pentosin ATF 84 provides exceptional anti-shudder performance with consistent and strong friction control properties, it is also supported by real-world testing with nearly 1,000,000 kilometers. Pentosin ATF 84 has been developed using selected base oil stocks, combined with specially formulated performance additive technology.

PRODUCT ATTRIBUTES

Appearance	Red
Density at 15°C	0.841 g/ml
Kinematic Viscosity at 100°C	4.5 mm ² /s
Kinematic Viscosity at 40°C	20.0 mm ² /s
Viscosity Index	140
Pour Point	-54°C/-65.2°F

SIZE	PART NUMBER	GTIN-13
1 Liter	1058114	4001541470808
5 Liter	1058216	4001541470815

OE REFERENCE NUMBERS/RECOMMENDATIONS

Make	Reference Number
Aisin Warner	AW-2
Audi / Volkswagen	G 060 540 A2
Audi / Volkswagen	G 053 001 A2
BMW	83 22 2 413 477 (ATF 7)
Ford	WSS-M2C949-AV
GM	Dexron ULV
Volvo	31492172

APPROVALS/SPECIFICATIONS

Organization Name	Specification Met
Asian Vehicles	JASO M315 TYPE 1A-LV
GM	Dexron ULV
Ford	Mercon ULV

Always consult the vehicle owner's manual to identify fluid specification requirements. MSDS available to professional repair technician upon request.

© CRP Industries Inc. Pentosin is a trade name of FUCHS Schmierstoffe GmbH. All rights reserved.

DISCLAIMER: CRP Industries Inc. has made every effort to assure the accuracy of the information on this product data sheet. Neither CRP Industries Inc., nor its affiliates assume responsibility for any loss or damage due to any errors, omissions, or manufacturing changes.

PENTOATF84-0124



AAE | REIN | PENTOSIN

OE-quality brands for import applications.