

TRANSMISSION  
FLUID



# PENTOSIN ATF 134 FE PLUS

Premium Performance Low Viscosity Automatic Transmission Fluid

## DESCRIPTION

**Pentosin ATF 134 FE Plus** is a premium performance ATF with reduced viscosity, especially developed to further optimize fuel-economy and gearbox efficiency of latest generation Mercedes-Benz 9-speed automatic transmissions. (Type 9-G Tronic). Not backwards compatible with previous MB-ATF-Specifications. The extremely low viscosity of Pentosin ATF 134 FE PLUS offers an enormous potential for fuel savings and very good low-temperature properties. The product also features low oil consumption and optimized friction coefficient stability.

## PRODUCT ATTRIBUTES

Appearance	Amber/Clear
Density at 15°C	0.822 g/ml
Kinematic Viscosity at 100°C	4.1 mm <sup>2</sup> /s
Kinematic Viscosity at 40°C	17.5 mm <sup>2</sup> /s
Viscosity Index	139
Pour Point	-45°C/-49°F

SIZE	PART NUMBER	GTIN-13
1 Liter	1090117	4001541464319
5 Liter	1090216	4001541464142

## OE REFERENCE NUMBERS/RECOMMENDATIONS

Make	Reference Number
Freightliner	MB 236.17
Mercedes-Benz	MB 236.17

Always consult the vehicle owner's manual to identify fluid specification requirements. MSDS available to professional repair technician upon request.

© CRP Industries Inc. Pentosin is a trade name of FUCHS Schmierstoffe GmbH. All rights reserved.

**DISCLAIMER:** CRP Industries Inc. has made every effort to assure the accuracy of the information on this product data sheet. Neither CRP Industries Inc., nor its affiliates assume responsibility for any loss or damage due to any errors, omissions, or manufacturing changes.

PENTOATF64-1022



OE-quality brands for import applications.