

MOTOR OIL



PENTOSPEED FE+ 0W-20

Premium Performance Engine Oil

DESCRIPTION

Pentospeed FE+ 0W-20 is uniquely formulated using XTL-technology (Xtreme Temperature Lubrication) in conjunction with state-of-the-art additive technology to provide a high performance engine oil. With reduced fuel consumption (up to 3.6%) and less CO₂ emissions, Pentospeed FE+ 0W-20 is one of the most innovative engine oils on the market. XLT-Technology allows improved aging stability in high speed driving and high outside temperature environments. Pentospeed FE+ 0W-20 offers protection against Low-Speed Pre-Ignition (LSPI) and outstanding wear protection in all operating conditions. It can be used in a variety of modern vehicles, especially in selected models from BMW, Mercedes-Benz, Opel and VOLVO, but also for a large number of Asian and American manufacturers (API SN PLUS RC & ILSAC GF-5).

PRODUCT ATTRIBUTES

Appearance	Clear
Density at 15°C	0.844 g/ml
Kinematic Viscosity at 40°C	41.4 mm ² /s
Kinematic Viscosity at 100°C	8.2 mm ² /s
Dynamic Viscosity at -35°C	5450 mPas
Dynamic Viscosity at 150°C	≥2.6 mPas
Flash Point	232°C/449°F
Viscosity Index	177

SIZE	PART NUMBER	GTIN-13
1 Liter	8044317	4001541231966
5 Liter	8044319	4001541231973

OE REFERENCE NUMBERS/RECOMMENDATIONS

Make	Reference Number
Chrysler	MS-12145
Fiat	9.55535-GSX
Ford	WSS-M2C947-A
Volvo	VCC RBS0-2AE

APPROVALS/SPECIFICATIONS

Organization Name	Specification Met
ACEA	C5
API	SN Plus RC
BMW	Longlife 14 FE+
ILSAC	GF-5
Mercedes	229.71
OV	040 1547

Always consult the vehicle owner's manual to identify fluid specification requirements. MSDS available to professional repair technician upon request.

© CRP Industries Inc. Pentosin is a trade name of FUCHS Schmierstoffe GmbH. All rights reserved.

DISCLAIMER: CRP Industries Inc. has made every effort to assure the accuracy of the information on this product data sheet. Neither CRP Industries Inc., nor its affiliates assume responsibility for any loss or damage due to any errors, omissions, or manufacturing changes.

PENTOLL14SAE0W20-0118



OE-quality brands for import applications.