HYDRAULIC FLUID



PENTOFLUID EHF

Long-Life Hydraulic Power Steering Fluid For Modern Vehicles

DESCRIPTION

Pentofluid EHF is a high performance hydraulic power steering fluid for lifetime application in modern vehicle aggregates. Pentofluid EHF is especially designed for hydraulics in the automotive industry with the highest technical requirements such as in: power steering, level control, shock absorber, hydro-pneumatic suspension, stability and traction control, hydraulics for convertible tops, central lock systems, etc. It is suitable for all extreme conditions and guarantees full performance from -40°C to over 130°C system temperature.

SIZE	PART NUMBER	GTIN-13
1 Liter	1405115	4001541458764

PRODUCT ATTRIBUTES	
Appearance	Dark Green
Density at 15°C	0.85 g/cm³
Kinematic Viscosity at 100°C	6.2 mm²/s
Kinematic Viscosity at 40°C	18.9 mm²/s
Kinematic Viscosity at -40°C	1400 mm²/s
Viscosity Index	315
Pour Point	-54°C/-65.2°F
Flash Point	145°C/293°F
Ignition Temperature	210°C/410°F

OE REFERENCE NUMBERS

Make	Reference Number
Audi/Volkswagen	G 002 000 A2
Bentley	RH 5000
BMW/MINI	82 11 0 148 132
BMW/MINI	82 11 1 468 041
BMW/MINI	83 29 0 429 576
Chrysler/Dodge/Jeep	05127381AB
Chrysler/Dodge/Jeep	68088485AA
Mercedes-Benz	001 989 24 03 10
Mercedes-Benz	001 989 24 03 12
Mercedes-Benz	Q 1 32 0001
Porsche	000 043 203 33
Saab	3032 380
Volvo	11 61 529

Always consult the vehicle owner's manual to identify fluid specification requirements. MSDS available to professional repair technician upon request.

© CRP Industries Inc. Pentosin is a trade name of FUCHS Schmierstoffe GmbH. All rights reserved.

DISCLAIMER: CRP Industries Inc. has made every effort to assure the accuracy of the information on this product data sheet. Neither CRP Industries Inc., nor its affiliates assume responsibility for any loss or damage due to any errors, omissions, or manufacturing changes.

CRP AUTOMOTIVE

AAE | REIN | PENTOSIN

OE-quality brands for import applications.