

BRAKE FLUID



PENTOSIN DOT 5.1 *EV READY*

Low Viscosity/Cold Conditions Brake Fluid

DESCRIPTION

Pentosin DOT 5.1 is an Ultra High-Performance Brake Fluid for hydraulic brake systems and clutch actuation in passenger cars, trucks, and motorcycles. DOT 5.1 is perfect for cold temperatures and offers safety against vapor lock. Excellent resistance to absorbing and retaining water and provides superior corrosion resistance. Ideal for all modern vehicles with ESP and ABS and can be used in all vehicles that require DOT 4 LV and lower DOTs. EV READY for all electric vehicles with hydraulic brake/clutch and ABS DSC systems.

PRODUCT ATTRIBUTES

Appearance	Amber
Density at 20°C	1064 kg/m ³
Kinematic Viscosity at 100°C	2.2 mm ² /s
Kinematic Viscosity at -40°C	≤ 750 mm ² /s
Wet Boiling Point	180°C/356°F
Dry Boiling Point	270°C/518°F

SIZE	PART NUMBER	GTIN-13
1 Liter	1244116	4001541470679
5 Liter	1244204	4001541470662

APPROVALS/SPECIFICATIONS

Organization Name	Specification Met
FMVSS	No. 116 DOT 5.1
ISO	4925 Class 6
ISO	4925 Class 7
SAE	J1704
Ford	WSS-M6C65-A2
Motorcraft	PM-20

Always consult the vehicle owner's manual to identify fluid specification requirements. MSDS available to professional repair technician upon request.

© CRP Industries Inc. Pentosin is a trade name of FUCHS Schmierstoffe GmbH. All rights reserved.

DISCLAIMER: CRP Industries Inc. has made every effort to assure the accuracy of the information on this product data sheet. Neither CRP Industries Inc., nor its affiliates assume responsibility for any loss or damage due to any errors, omissions, or manufacturing changes.

PENTODOT51-0524



AAE | REIN | PENTOSIN

OE-quality brands for import applications.