

MOTOR OIL



PENTOSPEED DEXOS1™ GEN3 5W-30

Ultra-High Performance Synthetic Engine Oil

DESCRIPTION

Pentospeed dexos1™ Gen3 5W-30 is a fully synthetic, ultra-high-performance motor oil developed specifically for General Motors gasoline engines requiring dexos1™ Gen3. Developed to provide Low-Speed Pre-Ignition (LSPI) protection and improved vehicle performance. Offers optimum cold start properties and aging stability for a very good fuel economy throughout the drain interval. Inhibits deposits in engines and turbochargers for reliable operation and reduced maintenance costs. Very low oil consumption due to minimized evaporation loss. Miscible with conventional branded oils, though a complete oil change is recommended to obtain full benefits. Meets ILSAC GF-6A, a specification widely used as a basis by leading manufacturers including Toyota, Honda, Hyundai/Kia, Nissan, Mazda, and Chrysler.

PRODUCT ATTRIBUTES

Appearance	Amber
Density at 15°C	0.85 g/ml
Kinematic Viscosity at 100°C	10.57 mm²/s
Kinematic Viscosity at 40°C	58.5 mm²/s
Pour Point	-42°C/-43.6°F
Viscosity Index	173

SIZE	PART NUMBER	GTIN-13
1 Liter	8044214	4001541470501
5 Liter	8044216	4001541470518

OE REFERENCE NUMBERS/RECOMMENDATIONS

Make	Reference Number
Chrysler	MS 6395
FIAT	9.55535-CR1
Ford	WSS-M2C929-A WSS-M2C946-A WSS-M2C946-B1 WSS-M2C961-A1
GM	6094M 4718M
ILSAC	GF-5

APPROVALS/SPECIFICATIONS

Organization Name	Specification Met
API	SN PLUS RC / SP RC
dexos1™ Gen3	D335AFDK075
ILSAC	GF-6A

Always consult the vehicle owner's manual to identify fluid specification requirements. MSDS available to professional repair technician upon request.

© CRP Industries Inc. Pentosin is a trade name of FUCHS Schmierstoffe GmbH. All rights reserved.

DISCLAIMER: CRP Industries Inc. has made every effort to assure the accuracy of the information on this product data sheet. Neither CRP Industries Inc., nor its affiliates assume responsibility for any loss or damage due to any errors, omissions, or manufacturing changes.

PENTOD1G35W30-0825



AAE | REIN | PENTOSIN

OE-quality brands for import applications.