

TRANSMISSION FLUID



PENTOSIN FFL-52529

Fully Synthetic Double Clutch Transmission Fluid

DESCRIPTION

Pentosin FFL-52529 is a premium performance DCTF specially developed for the wet clutch of the DL382 (OCK) transmission of VW group, especially used in the higher performance models of the VW and AUDI vehicles. It provides ultimate friction stability and best fuel economy properties.

PRODUCT ATTRIBUTES

Appearance	Amber/Clear
Density at 15°C	0.835 g/ml
Kinematic Viscosity at 100°C	5.5 mm ² /s
Kinematic Viscosity at 40°C	23.5 mm ² /s
Viscosity Index	180
Pour Point	-60°C/-76°F

SIZE	PART NUMBER	GTIN-13
1 Liter	1070107	4001541470822
5 Liter	1070207	4001541470839

OE REFERENCE NUMBERS/RECOMMENDATIONS

Make	Reference Number
Audi	G 055 529 A2
Volkswagen	G 055 529 A2

APPROVALS/SPECIFICATIONS

Organization Name	Specification Met
Audi	TL 52.529-C
Volkswagen	TL 52.529-C

Always consult the vehicle owner's manual to identify fluid specification requirements. MSDS available to professional repair technician upon request.

© CRP Industries Inc. Pentosin is a trade name of FUCHS Schmierstoffe GmbH. All rights reserved.

DISCLAIMER: CRP Industries Inc. has made every effort to assure the accuracy of the information on this product data sheet. Neither CRP Industries Inc., nor its affiliates assume responsibility for any loss or damage due to any errors, omissions, or manufacturing changes.

PENTOFFL8-0124



AAE | REIN | PENTOSIN

OE-quality brands for import applications.