BRAKE FLUID



PENTOSIN DOT 4 RS

High-Performance Racing Brake Fluid

DESCRIPTION

Pentosin DOT 4 RS is a high-performance brake fluid specially formulated for racing, motorsport, and other demanding applications where braking systems are exposed to extreme thermal loads. Its advanced formulation delivers exceptional resistance to vapor lock and brake fade, helping maintain consistent pedal feel and braking performance during demanding street and track use. Engineered for applications requiring uncompromising braking performance, Pentosin DOT 4 RS provides the thermal stability and reliability required when braking systems are pushed to their limits.

SIZE	PART NUMBER	GTIN-13
500 ML	4446114	810066521438

PRODUCT ATTRIBUTES	
Appearance	Straw
Density at 20°C	1078 kg/m³
Kinematic Viscosity at 100°C	2.59 mm²/s
Kinematic Viscosity at -40°C	1520 mm²/s
Flash Point	>120°C/>248°F
Ignition Temperature	>280°C/>536°F
Minimum Dry Boiling Point	>320°C/>608°F
Minimum Wet Boiling Point	>195°C/>383°F
pH Value	7.15

APPROVALS/SPECIFICATIONS	
Organization Name	**Specification Met**
FMVSS	No. 116 DOT 4

Always consult the vehicle owner's manual to identify fluid specification requirements. MSDS available to professional repair technician upon request.

© CRP Industries Inc. Pentosin is a trade name of FUCHS Schmierstoffe GmbH. All rights reserved.

DISCLAIMER: CRP Industries Inc. has made every effort to assure the accuracy of the information on this product data sheet. Neither CRP Industries Inc., nor its affiliates assume responsibility for any loss or damage due to any errors, omissions, or manufacturing changes.

AUTOMOTIVE
AAE | REIN | PENTOSIN
OE-quality brands for import applications.